

# Product sheet



## LEGRAND

SPD - protection of main distribution board - T1+T2 - limp 12.5 kA/pole - 1P

REF. 412270 | EAN. 3414970517364





> [Visit e-catalogue](#)

## Product characteristics

- Class I + II (T1+T2) low voltage SPDs - Protection against transient overvoltages for 230/400 V~ power networks (50/60 Hz). - SPDs compliant with EN/IEC 61643 - 11 standards - Recommended for main distribution boards - Class I+II (T1+T2) : SPDs tested and specified according to both T1 and T2 test classes
- SPDs for general protection of main distribution board - SPDs with plug-in modules and status indicators : - Green : SPD operational - Orange : plug-in modules to be replaced - Earthing systems : TT, TNC, TNST1+T2 - limp 12,5 kA/pole - For general protection of big installations and protection of small installations with external lightning protection (LPS) . - Up : 1.5 kV - I<sub>max</sub> : 60 kA/pole - U<sub>c</sub> : 320 V~ - Recommended MCB : DX<sup>3</sup> 63 A - C curve - Number of poles : 1P - I<sub>total</sub> (10/350) : 12.5 kA - Remote status monitoring (FS contact) : No - Number of modules : 1

## Documentation




### TECHNICAL DOCUMENTATION

-  F02060EN\_05.pdf | PDF (0.62Mo)
-  F02060FR\_06.pdf | PDF (0.61Mo)
-  EXB20026\_TG\_Surge\_Protective\_Devices\_EN.pdf | PDF (8.37Mo)
-  LE07561AA\_6.pdf | PDF (0.53Mo)

### CAD & Design specs / BIM

-  412220.dwg | DWG (0.18Mo)

### CATALOGUE PAGE & OTHERS

-  ex223001\_0087.pdf | PDF (0.12Mo)
-  ex223001\_0084.pdf | PDF (0.08Mo)
-  ex223001\_0088-0089.pdf | PDF (0.16Mo)

### Agreements & Certificates

-  OC / CB-AT 5098 | (0.22Mo)