

Product sheet



DPX³ 630 LEGRAND

Circuit breaker DPX3 630,3 poles, with rated current of 320A and rotary knob electronic protection unit.

REF. 422546 | EAN. 3414970383129

[> Visit e-catalogue](#)

Product characteristics

- Breaking capacity of 36kA, according to EN/IEC standard 60947 - 2, suitable for protection of high power industrial installations. Rated insulation voltage of 800V Rated impulse withstand voltage of 8kV
- Compliant with NEMA AB-1. Climatic condition according to IEC/EN 60947 - 1 Annex Q, Cat. F subject to temperature, humidity, vibration, shock and salt mist.
- Electronic protection unit with rotary knobs for regulation of thermal current and magnetic current. Thermal protection within range of 0,4 - 1,0 of the rated current. Magnetic protection within range of 1,5 - 10 of the rated current.
- Can be equipped with releases (undervoltage and shunt releases) and auxiliary contacts. Can be used with rotary handles or motor operator. Locking accessories are available.
- Has different type of possible connection accessories: cage terminals, spreader and rear terminals. Is available also in a plug-in version (circuit breaker fitted with special terminals and mounted on a plug-in base) or in a draw-out version (a plug-in version fitted with a "Debro-lift" mechanism which can be used to withdraw the breaker while keeping it on its base)

The product's benefits

Installation

- DPX3 platform has been developed to give a new solution of protection devices for a more precise approach in power installations in order to offer the correct answer for different project needs.

Usage

- DPX3 platform provide a complete "project" approach in premium market segment, offering a range completely suitable for high power application

Avantages

- DPX3 630 is the answer for the competition in the project sub-segment. A unique size for all versions (thermal magnetic, electronic with or without measure). Earth leakage features can be achieved by adding a dedicated module at the bottom of the breaker itself.


Documentation

TECHNICAL DOCUMENTATION


- [LE07037AB.pdf](#) | PDF (0.94Mo)
- [F01964FR01_DPX3_1600ELE_FRAv3.pdf](#) | PDF (0.7Mo)
- [LE08011AA.pdf](#) | PDF (0.44Mo)
- [EXB15015_TG_Coordination_EN.pdf](#) | PDF (5.41Mo)

CATALOGUE PAGE & OTHERS


- [ex223001_0181.pdf](#) | PDF (0.1Mo)
- [ex223001_0198.pdf](#) | PDF (0.03Mo)
- [ex223001_0196-0197.pdf](#) | PDF (0.52Mo)

 EXB19026_CA_DPX3_125HP250HP_630_1600EN.pdf | PDF
(82.93Mo)

 F01964EN02_DPX31600_ELE.pdf | PDF (3.03Mo)

 EXB21086_CA_DPX3HP125_250_DPX3630_1600FR.pdf | PDF
(83.49Mo)

CAD & Design specs / BIM

 422321.dwg | DWG (0.2Mo)